

CLAIMS

1. An apparatus for multi-pathway impedance characterization and ablative treatment of tumors, the apparatus comprising:

an elongated delivery device including a lumen, the elongated delivery device being maneuverable in tissue;

an impedance sensor array deployable from the elongated delivery device and configured to be coupled to at least one of an electromagnetic energy source or a switching device, the impedance array including a plurality of resilient members, at least one of the plurality of resilient members being positionable in the elongated delivery device in a compacted state and deployable with curvature into tissue from the elongated delivery device in a deployed state, the plurality of resilient members defining a sample volume in the deployed state, at least one of the plurality of resilient members including an impedance sensor, at least a portion of the impedance array configured to sample tissue impedance through a plurality of conductive pathways;

an energy delivery device coupled to one of the sensor array, the at least one resilient member or the elongated delivery device, the energy delivery device including at least one RF electrode; and

an advancement member coupled to the impedance array, the advancement member including an actuable portion, the advancement member configured to control deployment of at least a portion of the array.

2. An apparatus for vector impedance characterization and ablative treatment of tumors:

an elongated delivery device including a lumen, the elongated delivery device being maneuverable in tissue;

an impedance sensor array deployable from the elongated delivery device and configured to be coupled to at least one of an electromagnetic energy source or a switching device, the impedance array including a plurality of

resilient members, at least one of the plurality of resilient members being positionable in the elongated delivery device in a compacted state and deployable with curvature into tissue from the elongated delivery device in a deployed state, the plurality of resilient members defining a sample volume in the deployed state, at least one of the plurality of resilient members including an impedance sensor, at least a portion of the impedance array configured to measure an impedance vector within a selectable tissue site;

an energy delivery device coupled to one of the sensor array, the at least one resilient member or the elongated delivery device, the energy delivery device including at least one electrode or antenna; and

an advancement member coupled to the energy delivery device, the advancement member including an actuatable portion, the advancement member configured to control deployment of at least a portion of the energy delivery device.

3. The apparatus of claim 1 or 2, wherein the plurality of resilient members includes a first, a second and a third resilient member.

4. The apparatus of claim 1 or 2, wherein the sensor has a resistance gradient or a resistance gradient configured to improve measurement of a complex impedance.

5. The apparatus of claim 4, wherein the resistance gradient is along a length of the sensor and configured compensate for resistive losses or hysteresis along the length of the sensor.

6. The apparatus of claim 1 or 2, at least a portion of the impedance arrays is configured to measure at least one of an intracellular impedance, an interstitial impedance or an intercellular capacitance.

7. The apparatus of claim 1 or 2, wherein the impedance array is configured to determine a locus of impedance within the sample volume.

8. The apparatus of claim 1 or 2, wherein the impedance array is configured to sample an impedance of at least a portion of the sample volume.

9. The apparatus of claim 8, wherein the at least a portion includes a first portion and a second portion.

10. The apparatus of claim 9, wherein the impedance array is configured to substantially simultaneously measure a first impedance profile of the first portion and second impedance profile of the second portion.

11. The apparatus of claim 1, wherein the plurality of conductive pathways are configured to be substantially evenly distributed or spaced within the sample volume.

12. The apparatus of claim 1, wherein the plurality of conductive pathways includes a first pathway and a second pathway.

13. The apparatus of claim 12, wherein the impedance array is configured to substantially simultaneously measure a first impedance of the first pathway and second impedance of the second pathway.

14. The apparatus of claim 12, the first pathway is positioned at a selectable angle relative to the second pathway.

15. The apparatus of claim 12, wherein the first and second pathway have no common segments.

16. The apparatus of claim 12, wherein the first and second pathway have a common origin.

17. The apparatus of claim 12, wherein the first and second pathway have substantially the same pathway, the second pathway being in an opposite direction to the first pathway.

18. The apparatus of claim 1 or 2, wherein the impedance array is configured to detect at an indicator of cell necrosis.

19. The apparatus of claim 1 or 2, wherein the impedance array is configured to detect at least one of a tissue ablation volume, a cell necrosis volume, a tissue thermal volume or a tissue hyperthermic volume.

20. The apparatus of claim 1 or 2, further comprising:
logic resources coupled to one of at least a portion of the impedance array, the energy delivery device, the switching device or the electromagnetic source, the logic resources including a processor.

21. The apparatus of claim 20, wherein one of the impedance array or logic resources is configured to measure or analyze tissue impedance or complex impedance at a measurement frequency distinct from an RF ablation frequency.

22. The apparatus of claim 20, wherein the logic resources are configured to identify a tissue condition or differentiate tissue responsive to an impedance signal from the at least a portion of the impedance array.

23. The apparatus of claim 22, wherein the logic resources are configured to analyze the signal at a frequency having an increased tissue condition sensitivity relative to a frequency spectrum.

24. The apparatus of claim 20, wherein the logic resources are configured to distinguish between normal and abnormal tissue, the abnormal tissue including at least one of abnormally mutated tissue, abnormally dividing tissue, cancerous tissue, metastatic tissue or hypoxic tissue.

25. The apparatus of claim 20, wherein the logic resources are configured to distinguish between necrosed and non-necrosed tissue.

26. The apparatus of claim 20, wherein the logic resources are configured to analyze at least one of an intracellular impedance, an interstitial impedance an intercellular capacitance or a complex impedance.

27. The apparatus of claim 20, wherein the logic resources are configured to identify one of an inflection point, an asymptote, a minimum or a maximum of an impedance signal.

28. The apparatus of claim 27, wherein the logic resources are configured to identify at least one of an endpoint, an amount of tissue injury or a tissue type utilizing at least one of the inflection point, the asymptote, the minimum or the maximum of the impedance signal.

29. The apparatus of claim 20, wherein the logic resources are configured to identify an endpoint for an ablation procedure responsive to an impedance signal from the at least a portion of the impedance array.

30. The apparatus of claim 22, wherein the impedance signal includes at least one of an intracellular impedance, an interstitial impedance an intercellular capacitance or a complex impedance, the logic resources configured to identify a tissue condition utilizing at least one of an impedance

ratio including at least one of interstitial to intercellular impedance, real to imaginary impedance or impedance to capacitance.

5 31. The apparatus of claim 22, wherein the impedance signal is a complex impedance and the logic resources are configured to identify a tissue condition of the sample volume utilizing real and imaginary components of the complex impedance signal.

10 32. The apparatus of claim 20, wherein the impedance array is configured to substantially simultaneously measure an impedance of a first tissue volume portion and a second tissue volume portion and the logic resources are configured to compare the impedance of the first portion to an impedance of the second portion.

15 33. The apparatus of claim 2, the impedance array is configured to detect real and imaginary components of the impedance vector or magnitude and phase angle of the impedance vector.

20 34. An apparatus for multi-pathway impedance characterization and ablative treatment of tumors, the apparatus comprising:

 an elongated delivery device including a lumen, the elongated delivery device being maneuverable in tissue;

 an impedance sensor array deployable from the elongated delivery device and configured to be coupled to at least one of an electromagnetic energy
25 source or a switching device, the impedance array including a plurality of resilient members, at least one of the plurality of resilient members being positionable in the elongated delivery device in a compacted state and deployable with curvature into tissue from the elongated delivery device in a
30 deployed state, the plurality of resilient members defining a sample volume in the deployed state, at least one of the plurality of resilient members including

an impedance sensor, at least a portion of the impedance array configured to sample tissue impedance through a plurality of conductive pathways; and

an energy delivery device coupled to one of the sensor array, the at least one resilient member or the elongated delivery device, the energy delivery device including at least one electrode or antenna.

35. An apparatus for complex impedance characterization of tumors, the apparatus comprising:

an introducer including a lumen, the introducer being maneuverable in tissue; and

an impedance sensor array positionable in the introducer in a compacted state and deployable from the introducer to define a sample volume in a deployed state, the impedance array configured to be coupled to at least one of an electromagnetic energy source, logic resources or a switching device, the impedance array defining a sample volume in a deployed state, at least a portion of the impedance array configured to sample a complex tissue impedance through a plurality of conductive pathways and detect or measure an indicator of at least one of tumorous tissue or cell necrosis.

36. The apparatus of claim 35, wherein the impedance array includes a sensor, the sensor having one of a resistance gradient or a resistance gradient configured to improve measurement of a complex impedance.

37. An apparatus for impedance characterization and frequency directed RF ablative treatment of tumors, the apparatus comprising:

an elongated delivery device including a lumen, the elongated delivery device being maneuverable in tissue;

an impedance sensor array deployable from the elongated delivery device and configured to be coupled to at least one of an electromagnetic energy source or a switching device, the impedance array including a plurality of resilient members, at least one of the plurality of resilient members being

positionable in the elongated delivery device in a compacted state and
deployable with curvature into tissue from the elongated delivery device in a
deployed state, the plurality of resilient members defining a sample volume in
the deployed state, at least one of the plurality of resilient members including
5 an impedance sensor; and

an energy delivery device coupled to one of the sensor array, the at least
one resilient member or the elongated delivery device, the energy delivery
device including a plurality of RF electrodes configured to generate a
directional ablation zone responsive to an RF frequency.

10

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000